



Gresham Motorsports Park
26th Annual World Crown 300
November 13-15, 2009



Renegade (Street Stock) Rules and Specifications Package

Disclaimer

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. **NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATIONS OF OR COMPLIANCE WITH THESE RULES AND/OR REGULATIONS.** They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator, or official.

The race director shall be empowered to permit reasonable and appropriate deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. **NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM SUCH ALTERATION OF SPECIFICATIONS.** Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is final.

Sincerely,

The Management

Gresham Motorsports Park

Track Properties, LLC



Gresham Motorsports Park
26th Annual World Crown 300
November 13-15, 2009



Renegade (Street Stock) Rules and Specifications Package

Rules and Specifications

If the rules don't say you can ...then you can't

Street Stock

Competition is open to 1965 to 2001 models of American manufactured hardtop passenger cars with a minimum wheel base of 108" inches. Station Wagons are permitted. Wheel base must be stock for make and model of cars. Note: No camaros, firebirds, mustangs, or any pony type car or sports car. Leaf spring cars are eligible as long as they meet the other rules of this division. Only rear wheel drive cars permitted.

Car numbers must be painted in a minimum of 24" high numerals on side panels and on the roof in a contrasting color. All lettering and decals must be in good taste.

These cars are to remain stock for make and model.

Exhaust Manifold

1. No tube headers permitted.
2. Stock cast iron manifolds (O.E.M.) any model.
3. No after market exhaust manifolds permitted.
4. Exhaust manifold not to exceed 2 ¼" O.D.

Rear End

1. Stock for make and year model.
2. No locked rear ends permitted.
3. No positive traction rear ends permitted.
4. Maximum gear ratio 3.42

Transmissions

1. Transmission must be stock for make and model.
2. Any coolers must be in stock location. No modifications.

Body

Body must be acceptable to Gresham Motorsports Park officials at all times

1. No panels or bracing can be removed. Inner front fender wells may be removed.
2. Hoods and deck lids must have original hinges.
3. Doors must be welded or bolted.
4. All cars must have windshields made of 1/8" clear polycarbonate, rear window is optional.
All glass must be removed.
5. Headlights, taillights, and molding must be removed. No outside mirrors.
6. All bodies must be closed in rear.

Interior

1. The stock steel floor pan, fire walls, and trunk floor **MUST BE RETAINED. NO HULLING.**
2. Must have stock steering column in stock position. Quick release steering wheels permitted.
3. Minimum two point roll bars are required in driver's compartment. Round steel 1-¾ inch seamless bars .090 walls are compulsory. Roll bars must be welded. Must be approved by Gresham Motorsports Park Officials.
4. Racing Seats mandatory. Must be acceptable to track officials
5. Approved seat belts, shoulder harness, head and neck restraints are **MANDATORY.** Must have at least 3" safety belts and 2" shoulder harness. Belts cannot be over five (5) years old.
6. All roll bars surrounding driver must be padded. Padding must be acceptable to Gresham Motorsports Park Officials.



Gresham Motorsports Park
26th Annual World Crown 300
November 13-15, 2009



Renegade (Street Stock) Rules and Specifications Package

7. A window net must be installed in the left side door glass opening. The window net must be a rib type, made from nylon material with a minimum 1" square opening between the ribs. The minimum window net size shall be 22" wide by 16" high. All window nets must have quick release mechanism and be welded to roll cage. The window net, when in the closed position, must fit tight when secured.
8. Rear view mirror permitted inside of car only.
9. Metal piece to cover rear seat opening to trunk. Must be STEEL.
10. Fire suit and helmet required and extinguisher must be mounted within reach of driver.

Fuel

1. All competitors must use SONOCO 110 Purple.

Fuel System

1. Gas tank mounted in center of trunk between frame rails, strapped with 4-1" metal straps. The original gas tank must have 12 gallons of gas or less.
2. Fuel cell permitted, minimum ground clearance of 9".

Engine

1. Steel racing oil pans permitted.
2. Small block 350 Chevrolet, 351 Ford, and 340 Chrysler (No Small block 400 ci, No Big Blocks)
3. No Turbo. All components must be stock. No high performance cars or parts. Stock Cars ONLY.
4. Heads-70 cc minimum or stock for engine claimed.
5. Engine must be stock.
6. Stock type camshafts only .Lift at valve: Intake .410 Exhaust .410
7. Stock air cleaner. No K&N Air Filter, etc.

Ignition

1. OEM for make and model.
2. Batteries may be located in original position and securely fastened. Battery may be moved to heater box location or behind driver seats. Heater box may be removed if battery is put in that position.
3. Cars must start under their own power

Suspension

1. All chassis components must be stock for make and model.
2. Absolutely no moving "A" frame or cutting any cross-members. No lowering cars.
3. Suspension: Absolutely stock. No racing springs. Springs must be same size and height from right to left side. Springs cannot be cut. Must be stock diameter for make and model.

Driveshaft

1. Must be stock for make and model.
2. Must have driveshaft loop.

Tires and Wheels

1. Racing wheels, maximum 8 inches, permitted. Wheels must be centered offset. No aluminum wheels allowed. Mandatory racing wheel on right front.
2. Tires – Hoosier 890 ONLY.
3. Absolutely no altering, shaving, grooving, slicing, or soaking permitted. Any competitor found with altered tires in any fashion will be immediately disqualified from the event.
4. No part of the tire can protrude past the body of the car. Fenders cannot be flared or cut out.

Brakes

1. Brakes must be stock for make and model.
2. All brakes must be fully functional on all wheels.



Gresham Motorsports Park
 26th Annual World Crown 300
 November 13-15, 2009



Renegade (Street Stock) Rules and Specifications Package

Cooling System

1. Absolutely NO antifreeze. Any coolant fluids other than water must be approved by Gresham Motorsports Park Officials.

Limited to American made cars only.

No compact, convertibles, sports cars, pick-up trucks permitted. Weight limit minimum of 3100 lbs with driver before race. When adding weight to car it must be distributed equal left to right.

Schedule of Protest Fees

A- Head.....	\$400.00
B- Oil Pan.....	\$200.00
C- Check Fuel	\$100.00
D- Wheel Base.....	\$ 50.00
E- Left Side Weight.....	\$ 50.00
F- Suspension.....	\$100.00
G- Check fly wheel.....	\$200.00

Engine Claimer Rule \$1500.00—plus \$500.00 pull fee.

Refusing to sell engine will result in a 30 day suspension.

Only street stock competitors are permitted to buy an engine.

All engines that are claimed must be pulled out at track.

* Not included in the claim, are carburetor, water pump, pulleys, fuel pump, starter, spark plug wires, fly wheel, clutch, and pressure plate.